



CENTRAL VACUUM SYSTEMS
for Cleaner, Healthier, On-the-Road RV Living



65136



ALL-IN-ONE RETAIL PACKAGE
now includes the NEW powerful, easy-to-install Dirt Devil® CV950 LE Central Vacuum System and a space-saving accessory kit – ALL at the same low price!



Performance

- Creates a cleaner, healthier living environment
- Never recirculates vacuumed dust or odors

System

- UL/CSA certified
- Commercial grade quality
- High-performance motor
- Large one-gallon dirt capacity
- Convenient to use
- Dual filters
- Three-year warranty



DIRT DEVIL CENTRAL VACUUM SYSTEM

The Versatile Accessory Kit includes:

- FREE! RugRat® handheld powerhead
- 35' Crushproof expandable hose (stores at only 7')
- Swivel handle with air-relief valve
- Upper and lower wands
- Dusting brush
- Upholstery and Crevice tool
- 10" rug/floor tool
- 3 Disposable Bags

Bags made from an innovative 3-ply electrostatic material that captures the smallest dust and dirt particles (as small as .3 microns)!



62062


65008

- 65136** Dirt Devil CV950 LE Complete System #8233-LE 1
 - 65008** Deluxe Cleaning Tool Set (Includes 7' hose, expands to 30'; 2-piece wand set; rug, crevice, upholstery, dusting tool, plus the RugRat handheld turbine powerhead) #7829-BK 1
 - 62062** RV2000 & Dirt Devil Bags, Pk/3 #7767-W 1
- DISPOSABLE BAGS AVAILABLE.**
- 61432** For Small Wonder Vacuum Bags, Pk/3 #4908 1

QUIET, POWERFUL CLEANING PERFORMANCE THAT'S CONVENIENT AND EASY TO INSTALL!

The CV950 LE is a quiet, commercial-grade central vacuum system that can be installed in a basement, cabinet, under a seat or in a closet. This powerful system is convenient to use, features a high-performance motor and is covered by a 3 Year Warranty.

The CV950 LE Central Vacuum System also helps extend the life of furnishings and carpets while adding value to your RV or Trailer.



CV950 LE PRODUCT SPECIFICATIONS	
Weight	14 lbs
Dimensions	7.5"x7"x14.25"
Voltage	120 volts
Amperes	11.3
Motor	With overload and overheat protector; automatically resets when cooled
Dirt Capacity	1 gallon
CFM	120
Air Watts	450
Water Lift	105"

REFRIGERATOR REPLACEMENT MODELS

In Section J:	Vacuum	Refrigerators & Acc.	Dishwasher	Ranges & Acc.	Washer/Dryer	Water Heaters	Furnace	Fans	Air Conditioners	Generators
----------------------	--------	----------------------	------------	---------------	--------------	---------------	---------	------	------------------	------------

NORCOLD REPLACEMENT MODELS

I.D.	Norcold Model	Cut-Out Dimensions		
		H	W	D
A	322-323	20-5/8"	17-1/2"	21-1/4"
Ab	N260/N260.3	21"	19-3/8"	24"
B	N300/N300.3	29-3/4"	20-1/2"	21-3/8"
C	N400/N400.3	36-9/16"	23-11/16"	24"
D	N500/N500.3/N510/N510.3	42-5/8"	23-11/16"	24"
G	N641/N641.3	52-7/8"	23-1/2"	24"
J	N841/N841.3	59-7/8"	23-1/2"	24"
K	1200LR/LRIM	63-1/4"	32-11/16"	24"

YOUR REFRIGERATOR MODEL

Your Model	H	W	D	Replace with
DOMETIC RM24	22-3/8"	19-3/8"	19-7/8"	A
RM2150	17-1/2"	17-3/4"	21-1/2"	A
RM2191-2193	20-7/8"	17-3/4"	20-7/8"	A
RM2190	21-1/2"	17-3/4"	20-1/2"	A
RM211	22-11/16"	19-5/8"	17-5/8"	A
RM2202	22-1/4"	19-1/4"	18-1/4"	A
RM4223	21"	19-5/8"	24"	Ab
RM36	29-3/4"	20-1/2"	21-3/8"	B
RM360-361	29-3/4"	20-1/2"	21-1/4"	B
RM2300-2301	29-3/4"	20-1/2"	21-1/4"	B
RM2310.2/2310.3	29-3/4"	20-1/2"	21-3/8"	B
RM2332-2333	29-3/4"	20-1/2"	21-3/8"	B
RM45-46-47	31-1/4"	21-7/8"	23-5/8"	C
RM2460-461	32-3/8"	21-7/8"	23-3/4"	C
RM2400-2401	32-3/8"	21-7/8"	23-3/4"	C
RM2410	32-7/16"	23-3/16"	24"	C
RM2452-2453	36-9/16"	23-13/16"	24"	C
RM2551/2554	42-5/8"	23-11/16"	24"	D
RM2500-2501	40-1/4"	21-7/8"	24"	D
RM2510	40-5/16"	21-13/16"	24"	D
RM2510.2	40-5/16"	21-13/16"	24"	D
RM2552-2553	42-5/8"	23-13/16"	24"	D
RM3500-3501	38-1/4"	21-7/8"	24"	D
RM60-66-67	39-1/8"	21-7/8"	23-5/8"	D
RM660-661-663	40-1/2"	21-7/8"	23-3/4"	D
S1521-1531	42-3/4"	23-1/4"	24"	D
RM2600-2601	51-1/2"	21-7/8"	23-3/4"	G
RM2602-2603	49-9/16"	21-7/8"	24"	G
RM2604	49-1/2"	21-3/4"	24"	G
RM2607	49-1/2"	21-3/4"	24"	G
RM2652	53-3/4"	23-11/16"	24"	G
RM3600-3601	49-1/2"	21-7/8"	23-3/4"	G
RM3662-3663	53-3/4"	23-11/16"	24"	G
RM3607	49-1/2"	21-3/4"	24"	G
RM2610	51-1/2"	21-3/4"	24"	G
RM2611	49-1/2"	21-3/4"	24"	G
RM2612	49-1/2"	21-3/4"	24"	G
RM2620	49-1/2"	21-3/4"	24"	G
RM760-761-763	51-1/2"	21-7/8"	23-3/4"	G
S620-S630	52-5/8"	23-1/2"	24"	G
S1621-1631	52-11/16"	23-1/4"	24"	G
RM75-76-77	49-1/2"	21-7/8"	23-3/4"	G or J
RM2802-2803	64-1/2"	21-7/8"	23-3/4"	G or J
RM3800-3801	55-11/16"	21-3/4"	24"	G or J
RM100	51-1/2"	21-7/8"	23-3/4"	G or J
RM2804	53-3/4"	23-11/16"	24"	G or J
RM2607	49-1/2"	21-3/4"	24"	G or J
RM2807	55-3/8"	23-5/8"	24"	G or J
NDR1062	59-15/16"	23-11/16"	24"	J
RM2820	55-3/8"	23-5/8"	24"	J
RM2807	55-3/8"	23-5/8"	24"	J
RM2812	55-3/8"	23-5/8"	24"	J
RM2852	59-15/16"	23-11/16"	24"	J
RM1300-1301-1303	57-1/2"	23-3/4"	23-3/4"	J
RM3862-3863	59-15/16"	23-11/16"	24"	J
RM2800-2801	57-1/2"	23-3/4"	23-3/4"	J
RM4872-4873	58-15/16"	23-11/16"	24"	J
RM2810	57-5/16"	23-3/4"	24"	J

YOUR REFRIGERATOR MODEL

Your Model	H	W	D	Replace with
RM2811	55-3/8"	23-3/4"	24"	J
RM2812	55-3/8"	23-5/8"	24"	J
RM4804	63"	23-13/16"	24-1/16"	J
S820-S830	59-5/8"	23-1/2"	24"	J
S-1821	59-1/2"	23-1/4"	24"	J
S-1831	59-1/2"	23-1/4"	24"	J
NDR1272-RM1272	59-1/16"	36-3/4"	24"	K
NDR1282-RM1282	59-1/16"	36-3/4"	24"	K
NDR1292	59-1/16"	32-3/4"	24"	K
NDR1492	59-1/16"	36-1/2"	24"	K
RM7732	58-15/16"	32-11/16"	24"	K
RM77321M	58-15/16"	32-11/16"	24"	K
RM7832W	59-15/16"	23-11/16"	24"	K
HADCO HR-2	21-3/4"	19-3/16"	18-3/16"	A
HR3	28-3/8"	20-1/4"	19-5/8"	B
HR6	38-7/8"	21-5/8"	22-5/8"	C
HR4	31"	21-5/8"	22-5/8"	C
HR-7	56-1/2"	23-1/2"	23-3/8"	J
INSTAMATIC RV-2-201	21-3/4"	19-3/16"	18-3/16"	A
IM-2	22-1/4"	18-1/8"	18-5/8"	A
RV-3-301	28-3/4"	20-11/16"	19-7/16"	B
IM3	28-3/8"	20-1/4"	19-5/8"	B
RV-6-601	40-3/16"	22-5/16"	22-1/8"	C
IM160	40-1/4"	22"	22-3/4"	C
IM60	40-1/2"	24"	23"	C
IM6	38-7/8"	21-5/8"	22-5/8"	C
IM4	31"	21-5/8"	22-5/8"	C
IM140	31-1/4"	22"	22-3/4"	C
IM40	31-1/2"	24"	23"	C
RV-4-401	33-15/16"	20-11/16"	21-5/8"	C
IM270	51-3/4"	23-3/4"	23-1/4"	G
RV-7-701	53-1/8"	23-7/8"	23-1/4"	G
IM70	52"	24"	23"	G
IM7	56-1/2"	23-1/2"	22-3/8"	J
IM10	55-1/8"	23-1/2"	22-5/8"	J
RV8	59-5/16"	23-7/8"	23-3/4"	J
GE TG3	28-3/8"	20-1/4"	19-5/8"	B
TG4	31"	21-5/8"	22-5/8"	B
TG-5	38-7/8"	21-5/8"	22-5/8"	C
SIBIR RV104	30-5/16"	23-1/2"	23"	C
RV106	34-3/8"	23-1/2"	23"	C
RV240	34-1/8"	23-1/2"	23"	C
RV110	64-3/8"	23-1/2"	23"	J
RV280	59"	23-1/2"	23"	J
RV108	54-3/8"	23-1/2"	23"	J
RV270	54-1/16"	23-1/2"	23"	J
MAGIC CHEF R-88	51-1/4"	21-5/8"	22-3/4"	G
TR-82	56-1/2"	23-1/2"	22-3/4"	J
R-87	56-1/2"	23-1/2"	23-3/8"	J
NORCOLD 776	40-1/8"	22"	21-1/2"	C
875	40"	22"	21-3/4"	C
874	33"	22"	21-3/4"	C
774	33-1/8"	22"	21-3/4"	C
442/443	30-7/8"	23-1/2"	24"	C
6052/6053	43-1/4"	23-1/2"	24"	D
8652-8653	43"	23-5/8"	24"	D
778	52-1/8"	23-7/8"	24"	G
838	51-1/8"	23-15/16"	23-1/2"	G
876	52-1/8"	24"	24"	G
8662	52-1/2"	23-5/8"	24"	G
462-463/662-663	52-7/8"	23-1/2"	24"	G
6162/9162-9163	52-7/8"	23-1/2"	24"	G
878	59"	24"	24"	J
8010	59"	23-7/8"	24"	J
8310	58-7/8"	23-15/16"	23-1/2"	J
8682	59-1/2"	23-5/8"	24"	J
482-483/682-683	59-7/8"	23-1/2"	24"	J
6182/9182-9183	59-7/8"	23-1/2"	24"	J

* For more information on cooling units, please refer to section Q.



NORCOLD PORTABLE AC/DC REFRIGERATOR/FREEZERS

KEEP IT COOL, WHEREVER YOU GO!

Norcold's top performing AC/DC portables are dependable, energy efficient and exceptionally quiet. Whether you already have a refrigerator or get by with a cooler, you'll love being able to take the extras along with Norcold's multi-purpose, multi-use refrigerator/freezers.

- Refrigerators become a freezer with the turn of a dial. • Ideal second refrigerator or freezer. • Automatic temperature control. • Convenient lift-out storage basket. • Easy-access top loading. • Separate AC and DC cords. • Off-level operation up to 30°. • UL-approved components. • Charcoal & gray color.

MRFT-60, 2.12 cu. ft.

- Largest capacity portable available—up to 100 lbs. • Convenient dual-removable baskets separate food and drinks. • Automatically switches from DC to AC when AC is available. • 1.2-Amps @ 120-V/AC; 4.2/2.1-Amps @ 12/24-V/DC. • 70.5 lbs. net weight, 88 lbs. shipping weight.



67464

NORCOLD AC/DC FREE STANDING REFRIGERATOR/FREEZER—

FOR MOBILE AND MARINE USE

Norcold is the industry leader in marine refrigeration, with features like automatic conversion from AC to DC and back, low current draw, hermetically sealed and self-lubricating compressors, lightweight aluminum construction and handsome, sensible design.

- Free-standing model with mounting legs. • Full-width freezer compartment. • Exceptionally quiet, hermetically-sealed compressor. • Expressly designed for reliability in marine and mobile applications. • Easy, accessible storage. • Convenient, large container storage. • Durable and easy-to-clean white powder-coated shelves. • Easy open and close door latches—even under the counter. • Reversible door. • Off-level operation up to 30°.

DE0788B, 3.1 cu. ft.

- 3.1-cubic foot of storage. • Exceptionally-quiet, hermetically-sealed compressor - dependable without disturbing noise, even in close quarters! • Combination refrigerator-freezer. • Self-venting capability. • Flush, undercounter mounting. • Sharp black finish.



69238

Order #	Mfr. #	Description	Capacity	Un-Vented Enclosure Dimensions H x W x D	Vented Enclosure Dimensions H x W x D	Ship Code
67464	#MRFT60	Portable Refrigerator/Freezer	2.12 cu. ft.	N/A: Portable	17 ³ / ₈ " x 31 ¹ / ₄ " x 19 ¹ / ₄ "	◆
69238	#DE0788B	AC/DC Refrigerator	3.1 cu. ft.	30" x 21 ¹ / ₂ " x 20 ¹ / ₈ "	30" x 20 ¹ / ₂ " x 20 ¹ / ₈ "	◆

NORCOLD BUILT-IN REFRIGERATOR/FREEZER

AC/DC MODELS FOR MOBILE AND MARINE USE

A comprehensive line of top-performing AC/DC refrigerators for reliable performance in all mobile applications: boats, vans, trucks, RVs, and more! If it's time to upgrade your current refrigerator/freezer, you'll especially appreciate that these are more energy efficient, with an exceptionally quiet, hermetically sealed compressor—dependable without disturbing noise, even in close quarters. Built-in models have unfinished cabinets, and outstanding features:

- 12V fan aids airflow across condenser and compressor for improved cooling. • Easy, accessible storage with adjustable, removable door bins. • Durable and easy-to-clean white powder-coated shelves. • Convenient, large container storage. • Safe and stylish recessed doors. • Easy open and close door latches—even under the counter. • Reversible door. • Off-level operation up to 30°.

DE-0041 (2-WAY 12V DC/120 VAC), 3.6 cu. ft.

- Designed for an enclosure. • Convenient top-mounted automatic temperature control • Full-width freezer compartment. • Adjustable door bins hold various container sizes. • Black exterior trim; optional door panel *order 65551 panel*. • 0.2 Amps @ 120V/AC; 2.8/1.6 Amps @ 12/24 V/DC. • 75 lbs. net weight; 89 lbs. shipping weight.



65550

Order #	Mfr. #	Built-In Refrigerator	Capacity cu. ft.	Cut-Out Dimensions H x W x D	Ship Code	Order Door Panels Separately
65550	#DE0041R	AC/DC Flush Mount	3.6	30 ⁷ / ₈ " x 23 ¹ / ₄ " x 23 ¹ / ₂ "	◆	Single 65551



NORCOLD GAS ABSORPTION REFRIGERATORS ARE SIZED TO FIT YOUR NEEDS

In addition to leading the field in being compact, efficient and user friendly, these units have significant ergonomic touches to really enhance the vehicle.

N510 GAS ABSORPTION REFRIGERATOR FEATURES:

- **Largest capacity – 5.5 cubic feet – in its class.**
- Automatic re-ignites on gas if the flame goes out.
- Adjustable thermostat; set interior temperature to your preference.
- Thermostat backup system allows operation until service can be performed.
- Convenient eye-level electronic controls.
- Built-in control diagnostics provide valuable information to simplify servicing, speed repairs and increase customer satisfaction.
- Easy-clean, no-tarnish white powder-coated shelves.
- Adjustable middle shelf.
- Adjustable, removable door bins.
- 1-gal. container shelf storage; 2-liter bottle and 1/2 gal. door bin storage.
- Fresh fruit/vegetable storage bin/crisper.
- Flip-up bottom shelf holds gallon jug.
- Auto change over between gas and electric.
- Easily-reversible, self-latching door opens 150° and accepts side-installed decorative door panels.
- Travel latch with storage position.
- Latch can be mounted on top or bottom of door.
- Intergrated Cover/Baffle over controls.
- Automatic cycle to limit frost buildup on the refrigerator cooling fins.



Model	Amps 120V AC	Amps 12V DC	LP Gas
N410	2.0	—	Yes
N410.3	2.0	14.2	Yes
N510	2.0	.0.4	Yes
N510.3	2.0	14.2	Yes



N410 (2-way) and the N410.3 (3-way) 4.5 cu. ft. FEATURES:

- **Largest capacity — 4.5 cubic feet — in its class**
- Adjustable thermostat responds to changes in ambient temperature swings.
- Superior cooling performance.
- Convenient eye level controls.
- Freezer compartment.
- Easy to clean, no-tarnish white powder coated shelves.
- Adjustable, removable door bins.
- One-gallon container shelf storage, 2-liter bottle and 1/2 gallon door bin storage.
- Flip-up shelf accommodates gallon container.
- Manual change over between gas and electric.
- Self-latching reversible door opens 180°.
- Travel latch with storage position.
- Flame Current Meter monitors gas ignition.
- 84 lbs. net weight; 98 lbs. shipping weight.
- Made in America
- 1-year limited warranty.

Order #	Mfr. #	Built-In Refrigerator	Capacity cu. ft.	Cut-Out Dimensions	Door Panel Dimensions (not included)	
66392	#N410UR	2-Way - 120 VAC & LP Gas	4.5	36 ⁹ / ₁₆ "H x 23 ¹¹ / ₁₆ "W x 24"D	31"H x 21 ⁵ / ₁₆ "W x 3 ³ / ₁₆ "T	◆
66292	#N410.3UR	3-Way - 120 VAC, 12 VDC & LP Gas	4.5	36 ⁹ / ₁₆ "H x 23 ¹¹ / ₁₆ "W x 24"D	31"H x 21 ⁵ / ₁₆ "W x 3 ³ / ₁₆ "T	◆
65427	#N510UR	2-Way - 120 VAC & LP Gas	5.5	42 ⁵ / ₈ "H x 23 ¹¹ / ₁₆ "W x 24"D	37"H x 21 ⁵ / ₁₆ "W x 3 ³ / ₁₆ "T	◆
65428	#N510.3UR	3-Way- 120 VAC, 12 VDC & LP Gas	5.5	42 ⁵ / ₈ "H x 23 ¹¹ / ₁₆ "W x 24"D	37"H x 21 ⁵ / ₁₆ "W x 3 ³ / ₁₆ "T	◆



NORCOLD GAS ABSORPTION BUILT-IN REFRIGERATORS

These RV refrigerators are built to withstand the rigors of the road, as well as exposure to outdoor elements like dust, and dramatic changes in temperatures. "Two-Way" refrigerators are powered by 110 volt AC and LP gas, while "Three-Way" models also work on 12 volt DC. RV refrigeration systems use a gravity-fed evaporator to create the heat which ultimately cools, unlike a home refrigerator, which uses a compressor.



N641 (2-Way), N641.3 (3-Way)



N841 (2-Way), N841.3 (3-Way)



N841IM (2-Way with Ice Maker)

N600 AND N800 DIAGNOSTIC SERIES FEATURES:

- Superior Cooling Unit for top performance, greater durability and longer road life.
- Adjustable thermostat responds to changes in ambient temperatures and varied use.
- Embedded steel A-frame construction for structural integrity.
- One-gallon container shelf storage.
- Easy accessibility to two-liter bottle, half gallon and large container storage.
- Easy-clean, no-tarnish white powder coated shelves.
- Two crispers for storing ample meats, fruits and vegetables.
- Positive lock door handles—convenient, easy to use with either hand.
- Storage latches for air circulation when not in use.
- Light shuts off if door left ajar.
- Designed for built-in use (cabinet is unfinished).
- Convenient eye-level controls with built-in diagnostics.
- Black trim; add door panels (not included).
- 1-year limited warranty.
- Made in America.
- **N600 Series:** 120 lbs. net weight, 139 lbs. shipping weight.
- **N800 Series:** 129 lbs. net weight, 149 lbs. shipping weight.
- **N641 & N841:** 1.2 Amps @ 12V DC, 3.0 Amps @ 120V/AC, plus LP Gas.
- **N641.3 & N841.3:** 3.0 Amps @ 120V/AC, 14.8 Amps @ 12V/DC, plus LP Gas.

DOOR PANEL NOT INCLUDED; ORDER SEPARATELY

Order #	Mfr. #	Built-In Refrigerator	Capacity cu. ft.	Cut-Out Dimensions H x W x D	Ship Code	Black Door Panel Order Separately		
64963	#N641L	2-Way Diagnostic	6.3	52-7/8" x 23-1/2" x 24"	◆	Top	14-17/32" x 21-19/32"	61289
64614	#N641R	Diagnostic			◆	Bottom	31-5/8" x 21-19/32"	61294
64616	#N641.3R	3-Way Diagnostic	6.3	52-7/8" x 23-1/2" x 24"	◆	Top	14-17/32" x 21-19/32"	61289
						Bottom	31-5/8" x 21-19/32"	61294
64966	#N841L	2-Way Diagnostic	7.5	59-7/8" x 23-1/2" x 24"	◆	Top	14-17/32" x 21-19/32"	61289
64617	#N841R	Diagnostic			◆	Bottom	38-1/2" x 21-19/32"	61300
64618	#N841IMR	2-Way Diagnostic with Icemaker	7.5	59-7/8" x 23-1/2" x 24"	◆	Top	14-17/32" x 21-19/32"	61289
						Bottom	38-1/2" x 21-19/32"	61300
64621	#N841.3R	3-Way Diagnostic	7.5	59-7/8" x 23-1/2" x 24"	◆	Top	14-17/32" x 21-19/32"	61289
						Bottom	38-1/2" x 21-19/32"	61300

NORCOLD GAS ABSORPTION REFRIGERATORS

These RV refrigerators are built to withstand the rigors of the road, as well as exposure to outdoor elements like dust, and dramatic changes in temperatures. "Two-Way" refrigerators are powered by 110-volt AC and LP gas, while "Three-Way" models also work on 12-volt DC. RV refrigeration systems use a gravity-fed evaporator to create the heat which ultimately cools, unlike a home refrigerator, which uses a compressor.



- Easy-to-clean, durable white, powder-coated shelves. • Made in America.

323 (3-WAY), 1.7 cu. ft.

- Easy-to-operate manual controls with automatic gas ignition.
- Built-in, flange mounted.
- Adjustable, removable shelves with tall container storage.
- Easy-to-clean, durable white, powder-coated shelves.
- Taupe trim and door.
- 1-year limited warranty.
- **323:** 1.4-Amps @ 120-V/AC; 11.7-Amps @ 12-V/DC, plus LP Gas.
- 39 lbs. net weight; 50 lbs. shipping weight.



MODELS N260 AND N300 ALSO FEATURE:

- Adjustable thermostat to respond to high ambient temperatures and varied use.
- Adjustable, removable door bins.



N260.3 (3-WAY), 2.4 cu. ft.

- Built-in, flange mounted. • Superior cooling performance.
- 1-year limited warranty.
- Contemporary door design adds style.
- Beige color; no door panel required.
- **N260.3:** 1.4-Amps @ 120-V/AC; 11.7-Amps @ 12-V/DC, plus LP Gas. • 45 lbs. net weight; 53 lbs. shipping weight.

N300 (2-WAY) N300.3 (3-WAY), 2.7 cu. ft.

- Built-in, flange mounted.
- Superior cooling performance refrigerator/freezer.
- 1-year limited warranty.
- Contemporary top-mounted controls. • Beige color; accepts decorative door panels (not included). • **N300:** 1.5-Amps @ 120-V/AC; plus LP Gas; **N300.3:** 1.5-Amps @ 120-V/AC; 9.2-Amps @ 12-V/DC, plus LP Gas.
- 63 lbs. net weight; 72 lbs. shipping weight.



Order #	Mfr. #	Built-In Refrigerator	Capacity cu. ft.	Cut-Out Dimensions H x W x D	Ship Code	Door Panel Information
62897	#323TR	3-Way, Taupe color	1.7	20 ⁵ / ₈ " x 17 ¹ / ₂ " x 21 ¹ / ₄ "	◆	Included
64600	#N260.3R	3-Way, Beige color	2.4	21" x 19 ³ / ₈ " x 24"	◆	Included
64601	#N300R	2-Way, Beige color	2.7	29 ³ / ₄ " x 20 ¹ / ₂ " x 21 ³ / ₈ "	◆	Accepts door panels (not included)
64602	#N300.3R	3-Way, Beige color	2.7	29 ³ / ₄ " x 20 ¹ / ₂ " x 21 ³ / ₈ "	◆	Accepts door panels (not included)



RV DESIGNER PLUG FOR REFRIGERATOR DRAIN HOSE

Lets water out, keeps dirt & bugs from getting in. Clamshell packaging, 3" W x 5" H x 1" D.

44841 Plug for Fridge Drain Hose, PK/2
#E378 ZZ



JCJ ENTERPRISES MUD DAUBER SCREEN FOR REFRIGERATOR VENTS

Protective screen keeps out mud daubers, wasps, mice, birds and more, without blocking air flow. Heavy stainless steel—just install and forget. Package contains 3 screens plus plastic ties to easily attach to vent door cross bar.

Mud Dauber Screen for Refrigerator Vents:

65685 For Norcold #R-300 24

66590 For Dometic #R-600 24



NORCOLD AC/DC BUILT-IN REFRIGERATOR

All Norcold AC/DC Built-Ins

- Designed for reliable performance in all mobile applications: boats, vans, trucks, RVs, specialty vehicles and more!
- Exceptionally quiet, hermetically-sealed compressor that's dependable without disturbing noise, even in close quarters.
- Easy, accessible storage with adjustable, removable door bins.
- Convenient, large container storage.
- Durable, easy-to-clean white powder-coated shelves.
- Safe and stylish recessed doors.



DE-0061T AC/DC REFRIGERATOR

- 7.0 cu. ft. • Top-of-the-line, two-door model.
- Contemporary Flushmount™ styling.
- Self-ventilated design for easier integration.
- New! Interior light!
- Exceptionally quiet, hermetically-sealed compressor.
- Reversible, safe and stylish recessed doors.
- 12-volt fan aids airflow across condenser and compressor for improved cooling.
- Black exterior trim with optional door panel.
- Storage for varied sizes, including 2-liter, 1/2-gallon and 1-gallon containers.
- Adjustable, removable, large container door bin storage.
- Easy-clean, no-tarnish white powder-coated shelves.
- Easy open and close door latches - even under the counter.
- 0.4 Amps @ 120V/AC; 3.2/2.2 Amps @ 12/24 V/DC.
- Cut-out dimensions: 52-7/8" H x 23-1/4" W x 24-3/4" D; Net weight: 105 lbs.
- Two-year warranty.

65636 AC/DC Refrigerator #DE0061TR ◆1



CAMCO FRIDGE BRACE

Keep food from sliding as you go down the road. Helps keep cartons upright to reduce the risk of messy spills.

66606 Fridge Brace, Pk/2 #44033 4



Keeps your refrigerator door propped open to improve air circulation and prevent mold build-up. Simply moisten suction cups and place curved end on the inside of refrigerator side wall, close door to meet other end of PVC rod with its suction cup sticking to the inside of the door. Adjust to preferred opening position.

48154 Refrigerator Door Stay #45641 12



CAMCO RV OAK-FINISH REFRIGERATOR BARS

Keep order in your RV refrigerator and cupboards during travel. Spring loaded bars keep items in place. Cupboard bars extend from 10" to 17"; Refrigerator bars extend from 16" to 28".

68566 Refrigerator bars oak-look, Pk/3 #43823 6



JCJ ENTERPRISES SAFLOC RV FRIDGE DOOR LATCH

Safloc is an automatic locking device that keeps the refrigerator doors shut while traveling. It automatically locks, every time you close the door. Strong lifetime materials, easy-pull spring-loaded handle. Access to refrigerator is facilitated by a spring retained protruding handle.

45449 Safloc #M400 6

See section H for refrigerator vents



CONDOR by CP PRODUCTS MULTI-SURFACE SQUARE LEVEL

Great for use at home, or when you're on the road in your RV or camper. This multi surface level can be used on any of its edges to adjust vertical and restrictive areas. Carded.

40482 Multi-Surface Level #40482 20



RV DESIGNER PARTS FOR REFRIGERATOR

TRAVEL LOCK LATCH

Clever latch keeps fridge doors from opening while driving. Works for single or double door fig. 7/8" x 2". Black plastic. Screws included, Pk/2.

46178 Travel Lock Latch #H593 1

TRAVEL LOCK PIN

Pin fits in hole to lock fridge door closed while driving. Pin is 1-1/2" L. Chain & screw included.

46177 Lock Pin, Pk/1 #H591 1

Dinosaur Electronics

NEW!



DINOSAUR ELECTRONICS POWER SUPPLY BOARD

FOR NORCOLD REFRIGERATOR

2-way or 3-way. Operation: AC/DC/Gas. Replaces the following Norcold® part numbers: 618198, 618224, 618574, 618575, 618828, 619378. For older 900, 9100, and early 1200 series refrigerators. Just match Norcold's® board number to this board number for direct replacement.

60088 N991 Replacement Board for Norcold Refrigerator #N991 1

In Section J:	Vacuum	Refrigerators & Acc.	Dishwasher	Ranges & Acc.	Washer/Dryer	Water Heaters	Furnace	Fans	Air Conditioners	Generators
---------------	--------	----------------------	------------	---------------	--------------	---------------	---------	------	------------------	------------



64434



60604



64597

U-LINE ICE MAKERS

With the U-Line RV Ice Maker, there's no more inconvenience or embarrassment of running out of ice. The handsome 110-volt unit can put out over 1,000 ice cubes (20-23 lbs. worth) a day, and is also extremely energy efficient, consuming less than a 75-watt bulb in a month. Since it has a reversible-opening door and requires no drain, it's especially easy and inexpensive to install. It's completely automatic and features an interior storage bucket that holds up to 500 cubes at a time. 1/2" mounting flange all the way around. 64 lbs. shipping weight. Add 1/2" to depth dimension for water connection. 15-120 psi water pressure.

BLACK VINYL FRONT DOOR ICE MAKER

Customize the door of your icemaker. This stylish ice maker makes it easy for you to slide a custom insert into the slides on the front of the door. It's as easy as sliding a picture into a picture frame. Don't want a custom panel? Don't worry, the black finished background looks great all by itself. This U-Line ice maker produces an abundant supply of ice cubes in an amazingly short time: Makes over 23 lbs. of ice cubes daily from only 2-3/4 gallons of water and stores 12 lbs. of ice. It requires no drain and can be easily installed in any area (needs only a 1/4 inch outside diameter water line connection). Uses less electricity than a 75-watt light bulb. Comes with a field reversible door for left or right hinge, a black vinyl door panel, a 1/2" wide mounting flange for easy mounting in surrounding cabinets, an adjustable temperature control for adjustment of daily ice rate, corrosive and UV resistant components, see-through removable ice bucket, and a travel pin to keep door securely closed. Size: 25-1/4" H x 15-1/16" W x 17" D (w/flange) or 24-3/4" H x 13-13/16" W x 17" D (w/o flange). Weight: 65 lbs. 110/115 vac.

BLACK GLASS DOOR ICE MAKER

Our most popular ice maker. Stylish ice maker with a black glass door panel makes lots of ice — fast! This U-Line icemaker produces an abundant supply of ice cubes in an amazingly short time: makes over 23 lbs. of ice cubes daily from only 2-3/4 gallons of water and stores 12 lbs. of ice. It requires no drain and can be easily installed in any area (needs only a 1/4" outside dia. water line connection). Uses less electricity than a 75-watt light bulb. Comes with a field reversible door for left or right hinge, a 1/2" wide

mounting flange for easy mounting in surrounding cabinets, an adjustable temperature control for adjustment of daily ice rate, corrosive and UV resistant components, see-through removable ice bucket, and a travel pin to keep door securely closed. Size: 25-1/4" H x 15-1/16" W x 17" D (w/flange) or 24-3/4" H x 13-13/16" W x 17" D (w/o flange). Weight: 65 lbs. 110/115 vac.

64434 Standard Ice Maker with Black Vinyl Door Panel #B195BTP-03 1


60604 Standard Ice Maker with Black Glass Door #BCM95-03 1

64213 Solenoid Valve only #2552A 1

LOW PROFILE ICE MAKERS

Shorter size, big performance. Make lots of ice — fast! Short/low profile U-Line ice maker produces an abundant supply of ice cubes in an amazingly short time. Makes over 23 lbs. of ice cubes daily from only 2-3/4 gallons of water and stores 12 lbs. of ice. Requires no drain and can be easily installed in any area (needs only a 1/4" outside dia. water line connection). Uses less electricity than a 75-watt light bulb. Comes with a field reversible door for left or right hinge, a black glass door panel (64597), a 1/2" wide mounting flange for easy mounting in surrounding cabinets, an adjustable temperature control for adjustment of daily ice rate, corrosive and UV resistant components, see-through removable ice bucket, and a travel pin to keep door securely closed. Size: 18-7/8" H x 15-1/16" W x 24-13/16" D (w/flange) or 18-1/2" H x 13-13/16" W x 24-13/16" D (w/o flange). Weight: 68 lbs. 110/115 vac.

64597 Space Saving Ice Maker with Black Vinyl Door Panel #SP18B-03 1



49977

49978

DIGITAL MONITOR & CLOCK

REFRIGERATOR MONITOR & CLOCK

Keep track of your refrigerator temperature without opening the door and letting out all the cold air. This battery operated monitor mounts on the wall while a flat sensor runs to refrigerator. At any time you can switch to read the room temperature or turn the monitor into an easy to read digital clock. Not illuminated. Off-White. 3 1/4" L x 2 1/4" H x 1/2" D with bracket.

49977 Refrigerator Temperature Monitor & Clock #12-3020 10

TEMPERATURE MONITOR & CLOCK

Allows constant monitoring of outdoor or room temperature. Slide switch from thermo to clock and you have an easy-to-read digital clock. A simple sensor cable runs from monitor to outside. Battery operated. Not illuminated. 3 1/4" L x 2 1/4" H x 1/2" D with bracket. Off-White.

49978 Temp & Clock #12-3025 10

Dinosaur Electronics



DINOSAUR ELECTRONICS DOMETIC REPLACEMENT BOARD

- 2-way or 3-way operation. • Fuse protected.
- Variable temperature adjustment for Fixed Temp refrigerators. • CHECK light comes on after each ignition try fails to sense a flame.
- Repeats the 3 try ignition cycle at 30 minute intervals if no flame is sensed. • DC element will drop out and the DC mode light will flash in 3-ways if the voltage level falls too low for more than 10 seconds. • 3-yr. warranty.

**Use the 3850415.01 board only to replace previously properly installed Dometic® 3850415.01 boards; DO NOT USE 3850415.01 to replace any older Dometic® black boxes or the CDS#64846.*

67336 Dometic Replacement Board #3850415.01 REPLACEMENT 1

FOR NORCOLD REFRIGERATORS

POWER SUPPLY BOARD FOR NORCOLD OLD STYLE

- **64871** fits 652, 662, 662IM, 682, 682IM, 6052, 6082, 6162, 6182.

64871 2-Way #61647422 2-WAY 1



In Section J:	Vacuum	Refrigerators & Acc.	Dishwasher	Ranges & Acc.	Washer/Dryer	Water Heaters	Furnace	Fans	Air Conditioners	Generators
---------------	--------	----------------------	------------	---------------	--------------	---------------	---------	------	------------------	------------

DINOSAUR ELECTRONICS PARTS FOR DOMETIC REFRIGERATORS

TESTER FOR DOMETIC REFRIGERATOR BOARDS



A handy tool for troubleshooting newer Dometic refrigerators from the outside access panel. This tool plugs directly into the lower control module and quickly tests all functions of the refrigerator (AC/DC/GAS operation). In addition, the P-711 Exerciser will, through process of elimination, help you detect bad eyebrows and thermistors.

Compatible with the following refrigerator models: S1521, S1531, S1621, S1631, S1821, S1831, RM2607, RM2611, RM2612, RM2652, RM2807, RM2811, RM2812, RM2852, RM3607, RM3662, RM3663, RM3807, RM3862, RM3863, RM4872, RM4873, RM7030, RM7130, RM7732 and RM7832.

64898 Tester #P711 EXERCISER 1

THERMISTOR SIMULATOR

A handy new simulator used to determine if the Micro P-711 and all other Dometic® "black box" boards and their replacements are responding to thermistor changes. Plugs into the thermistor connector on the lower control board in back of the refrigerator. • 1-yr. factory warranty.



67337 Thermistor Simulator #THERMISTOR SIMULATOR 1



CONTROL BOARD - MICRO P-711

Use in Dometic RM 2607, RM2608, RM 2611, RM 2812, RM 2652, RM 2852, RM 3607, RM 3807, RM 3662, RM 3862, RM 3663, RM 3863, RM 4872, RM 4873, RM 7030, RM 7130, RM 7732, RM 7832

The Micro P-711 features a temperature adjustment knob that allows you to fine-tune the temperature of units equipped with a temp selector, and allows you to choose from the full range even with fixed-temp refrigerators. It is equipped with fuse protection on the 12v DC supply, DC element circuit, and 120 v AC circuit. It keeps the refrigerator operating if the eyebrow board or communication link fails keeping food safe and cool. The thermocouple unit eliminates ground bounce problems. Works in 2-way and 3-way units with all types of eyebrow. Easily installed by working in units with the wiring kit and without the wiring kit. All connections are clearly marked on the board.

64846 Micro P-711 #MICRO P-711 1

VALTERRA REFRIGERATOR FANS



FRIDGECOOL FAN

Air Circulator fan reduces food spoilage and cuts cool down time by 50%. Runs for more than 30 days on 2 "D" size batteries. Convenient easy on/off switch included.

66586 Fridgecool Fan with switch #A10-2606 6



FRIDGECOOL VENT FAN - UNIVERSAL MOUNT



"Wind Tunnel" design increases refrigerator cooling efficiency up to 40%. Fully automatic - only activates when fridge is on. Turns itself on at 100°, off at 80°. Can be mounted at the top of fridge rear compartment, or on the back of the refrigerator to blow air over the coils.

65161 Universal Mount Vent Fan #A10-2618VP 12

3-VOLT FAN

Stops sour milk, spoiled meat and frozen lettuce problems caused by poor air circulation in small RV or boat refrigerators... keeps air moving so food won't spoil. Small (about the size of a coffee cup).

60537 FridgeCool, 3 Volt #A10-2604 24



FRIDGECOOL SOLAR EXHAUST FAN

Efficient, long lasting single crystal solar panel will power the FridgeCool exhaust fan for years. Reduces inside refrigerator temperature by keeping refrigerator condenser fins cool and refrigerator operating at peak efficiency. Comes standard with 14' of wire, mounting screws and wire nuts.

67534 Solar Exhaust Fan #A10-2900VP 6

VESTA SPACE-SAVING DISHWASHER

The VESTA dishwasher not only offers the space, weight, and water savings that are so important, but they are built tough to withstand the rigors of the road. Vesta's handy dishwasher can be placed on top of a counter or built-in to a cabinet. Vesta offers normal wash cycles as well as a unique sanitizing cycle. Vesta's space-saving dishwasher leads the industry in installation, flexibility, efficiency and performance.

Features:

- Stylish, contoured door and see-through window.
- Four 4-piece place setting capacity.
- Cutlery Basket.
- Built-in self diagnostics.
- 5 Cycle wash (Intensive, Normal, Rapid, Eco, Pre-Wash).
- Detergent detent.
- Rinse aid dispenser.
- Stainless steel interior and reinforced case.
- Easy clean filter.
- Overflow flood protection.
- Electronic Controls w/LED's.
- LED Cycle Status Indicator.
- Pause/Start, & Delay Buttons.
- 1-yr. warranty.



SPECIFICATIONS:


- Model Type: DWV303DB
- Dim.: 22-1/2"W x 17-1/8"H x 18-5/8"D (57cm x 43.5cm x 47.3cm)
- Electrical: 120V, 10.6 Amp, 60Hz, 1280W
- Gross Weight: 49.5 lbs (22.45 kg)
- Max. Water Use: 1.43-2.74 gal (5.4-10.3 L)
- Safety Listing(s): UL/CSA
- Color: Black

67537 Dishwasher #DWV303DB 1

In Section J:	Vacuum	Refrigerators & Acc.	Dishwasher	Ranges & Acc.	Washer/Dryer	Water Heaters	Furnace	Fans	Air Conditioners	Generators
---------------	--------	----------------------	------------	---------------	--------------	---------------	---------	------	------------------	------------



WHIRLPOOL® MICROWAVES



0.7 CU. FT. COUNTERTOP MICROWAVE OVEN

FEATURES: • 0.7 Cu. Ft. Capacity
• 700 Watts Cooking Power
• 10-Level Variable Cooking Power Control
• Non-Sensor Cooking Cycles
• Non-Sensor Reheat, Defrost Cycles
• Staged Cooking
• Electronic Child Lockout Feature
• Removable Glass Turntable
• Braille Overlays and Special Needs Material Available
• Under The Cabinet (UTC) Mounting Bracket Included.

ELECTRICAL REQUIREMENTS:
15 or 20. 120. 60. AC-only. fused electrical supply is required. Grounded circuit is required. A time-delay fuse or circuit breaker and separate circuit is recommended.

DIMENSIONS:
11" H x 18" W x Depth: 12-3/8" D.
Dimensions shown are for planning purposes only. For complete information, see Installation Instructions packed with product.

67441 0.7 cu. ft. Countertop Microwave Oven, Black (Not shown) #MT4078SPB 1




1.1 CU. FT. COUNTERTOP MICROWAVE OVEN

FEATURES: • 1.1 Cu. Ft. Capacity
• 1,100 Watts Cooking Power
• 10-Level Variable Cooking Power Control
• Maxwave™ Cooking System
• Touch Control System
• Non-Sensor Cooking Cycles
• Non-Sensor Reheat, Defrost Cycles
• Electronic Child Lockout Feature
• Staged Cooking
• Warm Hold Cycle
• Jet Start™ Control - 30 Seconds
• Recessed Glass Turntable
• Optional Trim Kit Not Available for This Model.

ELECTRICAL REQUIREMENTS:
15 or 20. 120. 60. AC-only. fused electrical supply is required. Grounded circuit is required. A time-delay fuse or circuit breaker and separate circuit is recommended.

DIMENSIONS:
11-7/8" H x 20-1/8" W x 15-1/8" D.
Dimensions shown are for planning purposes only. For complete information, see Installation Instructions packed with product.

67442 1.1 cu. ft. Countertop Microwave Oven, Black #MT4110SPB 1



1.5 CU. FT. COUNTERTOP MICROWAVE OVEN

FEATURES: • 1.5 Cu. Ft. Capacity
• 1,200 Watts Cooking Power
• 10-Level Variable Cooking Power Control
• Maxwave™ Cooking System
• Touch Control System
• Sensor Cooking Cycles
• Non-Sensor Reheat, Cook, Defrost Cycles
• Staged Cooking
• Electronic Child Lockout Feature
• Warm Hold Cycle
• Jet Start™ Control - 30 Seconds
• Recessed Glass Turntable

ELECTRICAL REQUIREMENTS:
15 or 20. 120. 60. AC-only. fused electrical supply is required. Grounded circuit is required. A time-delay fuse or circuit breaker and separate circuit is recommended.

DIMENSIONS:
12-1/2" H x 21-7/8" W x 17-1/8" D.
Dimensions shown are for planning purposes only. For complete information, see Installation Instructions packed with product.

67443 1.5 cu. ft. Countertop Microwave Oven, Black (Not shown) #MT4155SPB 1
67444 Optional Trim Kit for 67443, Black; For a 27" opening #MK1157XVB 1



KITCHENAID ARCHITECT SERIES II SINGLE DISHWASHER DRAWER

Run small loads with the powerful performance of an independent dishwasher. A Pro Wash™ Bar supplements the wash arms by spraying water from the top throughout the dishwasher.

FEATURES: • 6 Cycles/4 Cycle Options
• Pro Wash™ Bar • Sure-Hold® Small Items Mesh Bag • Food Chopper • Sensor Wash • Pro Dry™ Feature • Removable Rack Inserts • 2 Sure-Hold® Light Item Clips • Nylon-Coated Stemware and Cup Holder • 2-Piece Silverware Basket
• Removable Nylon-Coated Racks with Cushion-Tip™ Tines • Whisper Quiet® Sound Insulation System (54 dBA)* • NSF® Certification
• ENERGY STAR® Qualified • Fully Integrated Console. *Per IEC standards, normal cycle.



FOR THE WAY IT'S MADE.™


SENSOR WASH:

An optional cycle that automatically selects the best temperature and cycle time based on the soil level of the dishes in the load.

ENHANCED RACK SYSTEM: Flexible, removable tines and a cup shelf help ensure thorough cleaning of every dish. Sure-Hold® Small Items Mesh Bag and two Sure-Hold® Light Item Clips provide secure placement of small contents.

DIMENSIONS: • Cut-out dim.: 23-1/2" L x 17 to 18-1/2"H x 24"D • Prod. dim.: 23-3/8" L x 17" H x 24" D; drawer pulls out to 19-1/4".

67391 Single-Drawer Dishwasher, Blk #KUDDO3STBL 1



For corner installation, there must be a 1/2" space between the adjacent cabinet doors (i.e. door knobs) and open dishwasher drawer.

In Section J:	Vacuum	Refrigerators & Acc.	Dishwasher	Ranges & Acc.	Washer/Dryer	Water Heaters	Furnace	Fans	Air Conditioners	Generators
---------------	--------	----------------------	------------	---------------	--------------	---------------	---------	------	------------------	------------



**WHIRLPOOL
RV GAS
RANGES**



- 9,100-BTU superburner with infinite heat control
- Two 6,500-BTU burners • Slanted control panel with easy-to-read graphics • Deep-well spill-catcher™ top • Multi-position nontilt chrome oven racks • Large-capacity oven with built-in broiler.

MAGIC CHEF – 16" AND 22" GAS RANGE

- Towel-bar handles and knobs that offer the same convenience and style as your range at home • High-gloss polished-aluminum burner heads with heavy steel cooktop grates • Scuff-resistant textured-steel surface • Steel door.

67371 16" Gas Range, Match-Light Ignition, Black #CLY1610BDB ◆ 1

67373 Bi-Fold Cover f/ 67371, Black #UXA1600BAB 1

Magic Chef, 22" Gas Range, Piezo Ignition, Blk:

67365 Steel Door #CLY2220BDB ◆ 1

67364 Glass Door #CLY2260BDB ◆ 1

67375 Bi-Fold Cover f/ 67365 & 67364, Black #UXA2200BAB 1



67366 shown with Bi-Fold Cover (Sold separately)



AMANA - 22" GAS RANGE

- Sealed burners • Twin continuous-flow heavy-duty removable grates • Piezo spark ignition • Color-matching glass oven door with towel-bar handle • Removable oven bottom.

67366 Black #ALY2280BDB ◆ 1

67377 Bi-Fold Cover f/67366, Black #UXA2280BAB 1


**BI-FOLD COVERS FOR
GAS COOKTOP OR RANGE**

- Convenient back splash when folded.
- Textured-steel cover • Unfolds to create added space when cooktop is not in use • Black.

67373 F/67371 #UXA1600BAB 1

67375 F/67361-67364 & 67365 #UXA2200BAB 1

67377 F/67362-67366 #UXA2280BAB 1



67375; Shown on Range (Sold separately)

67377; Shown on Cooktop (Sold separately)



67361



67362 Shown with Bi-Fold Cover; Sold separately.

RV 3-BURNER GAS COOKTOPS

- 9,100-BTU superburner with infinite heat control • Two 6,500-BTU burners
- Slanted control panel with easy-to-read graphics • Deep-well spill-catcher™ top.

MAGIC CHEF

- High-gloss polished-aluminum burner heads • Scuff-resistant textured-steel surface • Heavy steel cooktop grates.

67361 Black #CLZ8560ADB 1

67375 Bi-Fold Cover f/ 67361, Black #UXA2200BAB 1

AMANA

- Twin continuous-flow heavy-duty removable grates • Piezo spark ignition.

67362 Black #ALZ8580ADB 1

67377 Bi-Fold Cover f/67362, Black #UXA2280BAB 1



**SUBURBAN
2 & 3 BURNER STAINLESS STEEL
DROP-IN COOKTOPS**



Drop-in two- and three-burner Suburban RV Cooktops add compact, high-efficiency cooking performance to any motorhome, travel trailer, van or larger camper. Cooktops meet most manufacturer and installer size requirements. Suburban drop-in cooktops are designed with the same quality standards as their furnaces and water heaters. Drop-in two-burner model features 6,500-BTUH burners with front right controls. Drop-in three burner model features a 6,500-BTUH burner in front and two 5,200-BTUH burners in back with front right controls. Stainless steel top. Match-light top burners. One-piece, rattle-free grates are made of sturdy, heavy-gauge, porcelain-enameled steel. Grates remove easily for cleaning. Optional covers available.


Cut-out size, 2-burner: 16-3/8" W x 11-5/8" D x 3-1/8" H; set back 3/4" from front of counter.

Cut-out, 3-burner: 18-15/16" W x 16-1/8" D x 3-1/8" H; set back 2-3/8" from front of counter.

Drop-In Cooktop:

57259 2 Burner, Stainless Steel Top, 16³/₈" W x 11⁵/₈" D x 3¹/₈" H (Cover is Mfr#2946AST; sold separately) #2937AST 1

57261 3 Burner, Stainless Steel Top, 18¹⁵/₁₆" W x 16¹/₈" D x 3¹/₈" H (Cover is Mfr#2948AST; sold separately) #2938AST 1



GRATE CLIPS

60657 Pkg. of 8 Grate Clips for Magic Chef #MAG 50-20251-1MC 1

ROUND STYLE GRATE FOR WEDGEWOOD

67146 Round Style Grate #56378 1

RANGES, COOKTOPS & ACCESSORIES


MAJOR APPLIANCES **J**

In Section J: Vacuum Refrigerators & Acc. Dishwasher Ranges & Acc. Washer/Dryer Water Heaters Furnace Fans Air Conditioners Generators

65826
with Cover
(sold separately)



65835



Atwood[®] ATWOOD/WEDGEWOOD VISION™ DROP-IN COOKTOPS

Stylish lightweight drop-ins designed for when weight restrictions and tight space are a concern. The two-burner features one 7200 BTU burner with a large, oval grate and one 5200 BTU burner with standard circular grate. The three-burner features one 7200 BTU burner with a large, oval grate and two 5200 BTU burners with circular grates. A cover with windguards is also available as a special order.

Description	A (in.)	B (in.)	C (in.)	D (in.)	E (in.)	F (in.)	G (in.)	H (in.)
2-BURNER DIMENSIONS								
Burner Box	16.13	11.38	—	—	—	—	—	—
Counter Top Cutout	16.25	11.5	3.75	2.63	1.5	3.38	2.81	20.25
Top	18.00	13.00	—	—	—	—	—	—
Clearance to Combustibles from Edge of Cooktop: • Sides, 1.75" L, 2.5" R; • Rear, 3.06"; • Top, 20.25"; • Front: .75".								
3-BURNER DIMENSIONS								
Burner Box	18.88	14.88	—	—	—	—	—	—
Counter Top Cutout	19.00	15.00	4.5	3.06	3.0	2.0	2.81	20.25
Top	20.50	16.75	—	—	—	—	—	—
Clearance to Combustibles from Edge of Cooktop: • Sides, 2.25" L, 1.25" R; • Rear, 3.72"; • Top, 20.25"; • Front: .20".								

2-BURNER

The two-burner features one 7200 BTU burner with a large oval grate and one 5200 BTU burner with a standard circular grate.

DV20 2-Burner Drop-In Cooktop:

- 65821 Black #56493 1
- 65833 Stainless #56494 1

3-BURNER

The three-burner features one 7200 BTU burner with a large oval grate and two 5200 BTU burner with a standard circular grate.

DV30 3-Burner Drop-In Cooktop:

- 65826 Black #56471 1
- 65835 Stainless #56472 1

ATWOOD/WEDGEWOOD RV SERIES RANGES

Wedgewood high output ranges deliver style and power to home cooking on the road. These ranges are made with a wide door for a residential look, a single grate piece which allows the cook to slide pans from burner to burner, linear valves, and individual ignitors. Additional features include: 9,000 BTU high output main burner and enhanced 6,500 BTU rear burners, centralized high output burner and improved flame distribution, spacious, high-efficiency 17" or 21" ovens, built-in broiler/toaster section, and a variety of colors. Note: when replacing an old R series range, include the 64634 trim strip.



17" 3-Burner Range, 17³/₄" D x 20¹/₄" W x 16" H:

- 64797 White Door #82384 1
- 62941 Black Glass Door #52382 1

21" 3-Burner Range, 17³/₄" D x 20¹/₄" W x 20" H:

- 64801 White Glass Door #52245 1

Trim Strip only:

- 64634 LS Trim Strip F/Range #56188 1



SUBURBAN RANGES

22" Suburban gas RV range offers high efficiency, well insulated oven with an especially large broiler. The tall oven heats to 450° and contains a sturdy, easy-sliding oven rack with multiple rack positions. Porcelain oven and broiler pan surfaces are smooth and rounded for easy cleaning. The door is black textured steel. The piezo ignition creates a spark to light the cooktop burners. No need for matches. Turn the burner knob for gas, then turn the piezo knob to ignite the burner quickly and easily. It also features a high-output, 9,000-BTU/h front burner with linear valve. Smooth, infinitely variable flame adjusts from a gentle simmer to high heat for faster cooking. Two 6,500-BTU/h rear burners add lots of cooking capacity. One-piece porcelain-coated steel grate is more convenient for large pans or griddles. Lifts off fast for easy, quick cleaning of the entire cooktop.

- Cut-out size: 20-5/8" W x 21-3/4" H x 18-5/8" D.
 - Two-year limited mfr. warranty.
- The optional Range Cover provides additional counter space when the cooktop is not in use. Standard bi-fold cover is available in black.

- 57209 3-Burner Range, Black Top, Black Door, Model SRN3LBBE #2870A 1

- 56986 Range Cover, Black, for SRN Series 3-Burner Range #2814A 1

Suburban Range Replacement Parts:

- 64604 LS Grate Clip #121910 1

- 64608 Knob, Burner (SD2-SD3) #140219 1

- 67296 Grommet (SRN3LWBE) #071087 1

- 67297 Rubber Pad (SRN3LWBE, SS 2Burner Drop-In) #140214 1

- 67298 Igniter (SRN3LWBE,) #232577 1

In Section J:	Vacuum	Refrigerators & Acc.	Dishwasher	Ranges & Acc.	Washer/Dryer	Water Heaters	Furnace	Fans	Air Conditioners	Generators
---------------	--------	----------------------	------------	---------------	--------------	---------------	---------	------	------------------	------------

VENTMATE REPLACEMENT 6" FAN BLADE



6" fan blades for 12-v powered roof vents and range hoods. White, impact-resistant plastic. Direction of spin is determined by looking down through the motor, at the top of the blade.

65491 Current Ventline, 3/32" Round Bore, CCW, CD/1 #65491 1



SEE SECTION "B" FOR ADDITIONAL COOKING PRODUCTS

HONG'S

HENG'S EXTERIOR VENT OUTLET COVER

FOR JENSEN DUCTED RANGE HOODS

UV and weather resistant. Easy to install. Mounting hardware not included. Dimensions: 6" x 13". Cutout: 4" x 11".

Durable Standard Vent Cover with Damper:

66289 Bright White #J116AWH-C 60

62810 Colonial White #J116AOW-C 60



VENTLINE DUCTLESS RANGE HOOD

Constructed of heavy-gauge steel. Single-speed operation from 115V motor through directional louvers diverts air away from cooking area. Large light improves illumination. No duct required. Size: 12" H x 30" W x 12" D.

Ventless Range Hood Replacement Parts:

68580 4-Position Rotary Switch #BCB0164-00 1

66030 Pushbutton Switch #BV0199-04 1

69749 NEW! 12V Repl. Motor Kit; Included in the kit is the VD0218 motor, motor lead wires, screws, instruction sheet and a drill template to retro-fit the VD0218 motor to the brackets used with the older motors (screw hole spacing is different) #BVD0218-00 1

61100 120 Volt Motor for range hoods, 100 cfm #BVD0276-00 1

65254 LS Fan Blade, 110V range hood, 4-blade CCW; fits .214 dia. round shaft with knurl; 6-7/8" dia.; black #BCD0409-00 1



EXTERIOR VENTS FOR VENTLINE DUCTED RANGE HOODS

64357, 61898



61126

Weatherproof outside vent features a lockable damper, heavy styrene construction and a 3 3/4" inlet flange. Rough opening is 3 3/4" x 10 1/2". Overall size 11 5/8" x 5 9/32".

Horizontal Outside Vent:

64357 Colonial White #V2111-11 24

61898 Polar White #V2111-13 24

Louvered design. 1-3/4" inlet size. Durable injection molded plastic. Colonial white.

61126 Exterior Vent with louver design, Colonial White; Cutout: 10 1/2" x 3 3/4"; Overall: 12 1/8" x 5 1/4" x 1 3/4" #V2018-02 20

JCJ ENTERPRISES MUDDAUBER SCREEN FOR RV RANGE HOOD

The S900 Mud Dauber screen fits over existing Magic Chef, Atwood/Wedgewood and Suburban range hood vents, louvered style.

65635 Mud Dauber Screen #S-900 6



VENTLINE POWER RANGE HOODS

Enclosed light for full-range surface illumination. Switches easy to reach; washable lifetime grease filter. High-volume air output; quiet motor. Pre-wired for installation. For horizontal discharge. Size: 12" x 20" X 5" high.

110 Volt Power Range Hood:

61106 Almond #PH41-20AC-1 1

60108 White #PH41-20WC-1 1

12 Volt Power Range Hood:

61107 Almond #PH21-20A-1 1

60109 White #PH21-20W-1 1

Power Range Hood Parts & Accessories:

61126 Exterior Vent with louver design, Colonial White; Cutout: 10 1/4" x 3 3/4"; Overall: 12 1/8" x 5 1/4" x 1 3/4" #V2018-02 20

69749 NEW! 12V Repl. Motor Kit; Included in the kit is the VD0218 motor, motor lead wires, screws, instruction sheet and a drill template to retro-fit the VD0218 motor to the brackets used with the older motors (screw hole spacing is different) #BVD0218-00 1

61100 120 Volt Motor for range hoods, 100 cfm #BVD0276-00 1

68580 4-Position Rotary Switch #BCB0164-00 1



HENG'S INDUSTRIES HONG'S JENSEN 12V POWER RANGE HOOD

Quiet axial fan draws smoke and heat. Telescoping duct with damper and louver furnished. Heavy-gauge sheet steel. Enclosed light. Easy-to-clean removable filter. Easy-to-read exterior rocker style switches: away from grease and heat. Pre-assembled, pre-wired. Interchangeable with Jensen non-power hoods. Rear wall opening guides outside wiring assist installer. 20"L x 5"H x 18"D. Each range hood is boxed and includes the J116 (#62810) white outlet.

60199 Range Hood with Fan and Light, Almond #R0421200-C1C1 1

Replacement Parts:

67249 12V Motor, with D Shaft #90037-C1 5

